

PRODUCT SPECIFICATIONS	
Diameter	37mm (1.45 in)
Length	133mm (5.25 in)
Projectile Count	21
Velocity	96 m/s (315 fps)
Minimum Safe Distance¹	1.5m (5 ft)
Maximum Effective Distance	15m (45 ft)
PROJECTICLE SPECIFICATIONS	
Material	Rubber
Height	N/A
Diameter	15mm (0.6 in)
Weight	55 grams (1.9 oz)
Part Number	ALS3760
Warranty	5 years from date of manufacture

1 – When using this round at or near the minimum safe distance, the operator must evaluate the totality of circumstances (i.e. judgment, discretion, common sense) in relation to officer factors/judgment (i.e. subject factors, environmental factors, unknown factors, etc.) to determine whether or not deploying the round is appropriate for the situation.

PRODUCT DESCRIPTION	
The ALS3760 is a 37/40mm area fire round that can be direct or skip fired, producing blunt trauma and pain compliance. The round is most effective when used within the optimal range of 2-15 yards. Operators should be well trained in the use of Less Lethal munitions regarding shot placement including, but not limited to, factors such as: level of threat, target distance, and clothing. The optimal range allows for accurate targeting of the large muscle groups of the subject providing sufficient pain stimulus while greatly reducing the risk of serious or life-threatening injuries.	
SHIPPING INFORMATION	
UN Number	UN0012
Proper Shipping Name	Cartridges for weapons, inert projectile
Hazard Class	1.4S
Quantity per package	24
Total package weight	5.4kg (12 lb)
Package type	4G Cardboard Box
Package dimensions	425mm x 178mm x 140mm 16.75 x 7 x 5.5 inches

WARNING: This round should only be used by individuals properly trained in the use of specialty impact munitions. Serious injury or death may occur if this product is misused in rare or unexpected instances. Individuals should only engage appropriate target areas.

4700 Providence Road
Perry, FL 32347