



PRODUCT SPECIFICATIONS		
Diameter	40mm (1.57 in)	
Length	122mm (4.8 in)	
Projectile Count	3	
Velocity	96 m/s (315 fps)	
Minimum Safe Distance¹	1.5m (5 ft)	
Maximum Effective Distance	18m (60 ft)	
PROJECTICLE SPECIFICATIONS		
Material	Rubber	
Height	22mm (0.9 in)	
Diameter	36mm (1.40 in)	
Weight	17.25 grams (0.6 oz) ea 51.75g (1.82g) total	
Part Number	ALS4005	
Warranty	5 years from date of manufacture	
<p>1 – When using this round at or near the minimum safe distance, the operator must evaluate the totality of circumstances (i.e. judgment, discretion, common sense) in relation to officer factors/judgment (i.e. subject factors, environmental factors, unknown factors, etc.) to determine whether or not deploying the round is appropriate for the situation.</p>		
PRODUCT DESCRIPTION		
<p>The ALS4005 Interlocking Rubber Baton is a 40mm round that can be direct or skip fired, producing blunt trauma and pain compliance.</p> <p>The round is most effective when used within the optimal range of 2-20 yards. Operators should be well trained in the use of Less Lethal munitions regarding shot placement including, but not limited to, factors such as: level of threat, target distance, and clothing. The optimal range allows for accurate targeting of the large muscle groups of the subject providing sufficient pain stimulus while greatly reducing the risk of serious or life-threatening injuries.</p>		
SHIPPING INFORMATION		<p>WARNING: This round should only be used by individuals properly trained in the use of specialty impact munitions. Serious injury or death may occur if this product is misused in rare or unexpected instances. Individuals should only engage appropriate target areas.</p>
UN Number	UN0012	
Proper Shipping Name	Cartridges for weapons, inert projectile	
Hazard Class	1.4S	
Quantity per package	24	
Total package weight	5.4kg (12 lb)	
Package type	4G Cardboard Box	
Package dimensions	425mm x 178mm x 140mm 16.75 x 7 x 5.5 inches	 4700 Providence Road Perry, FL 32347