

| PRODUCT SPECIFICATIONS | |
|------------------------------------|----------------------------------|
| Diameter | 40mm (1.60 in) |
| Length | 102mm (4 in) |
| Projectile Count | 1 |
| Velocity | 100 m/s (325 fps) |
| Minimum Safe Distance ¹ | 1.5m (5 ft) |
| Maximum Effective Distance | 36.6m (120 ft) |
| PROJECTICLE SPECIFICATIONS | |
| Material | Polyurethane |
| Height | 73mm (3 in) |
| Diameter | 40mm (1.6 in) |
| Weight | 24 grams (1.0 oz) |
| Payload Weight | 3 grams CS |
| Part Number | ALS4006DCS |
| Warranty | 5 years from date of manufacture |



1 – When using this round at or near the minimum safe distance, the operator must evaluate the totality of circumstances (i.e. judgment, discretion, common sense) in relation to officer factors/judgment (i.e. subject factors, environmental factors, unknown factors, etc.) to determine whether or not deploying the round is appropriate for the situation.

PRODUCT DESCRIPTION

The ALS4006DCS REACT round is a direct fire round designed to combine blunt trauma pain compliance with CS tear gas irritant effect.

The round is most effective when used within the optimal range of 2-40 yards. Operators should be well trained in the use of Less Lethal munitions regarding shot placement including, but not limited to, factors such as: level of threat, target distance, and clothing. The optimal range allows for accurate targeting of the large muscle groups of the subject providing sufficient pain stimulus while greatly reducing the risk of serious or life-threatening injuries.

SHIPPING INFORMATION

| | | |
|----------------------|---------------------------------|---|
| UN Number | UN0301 | WARNING: This round should only be used by individuals properly trained in the use of specialty impact munitions. Serious injury or death may occur if this product is misused in rare or unexpected instances. Individuals should only engage appropriate target areas. |
| Proper Shipping Name | Ammunition, Tear Producing | |
| Hazard Class | 1.4G | |
| Quantity per package | 52 | |
| Total package weight | 8.17kg (18 lb) | |
| Package type | UN1A2 Steel Drum | |
| Package dimensions | 305mm x 406mm 12 x 16 inches | |



4700 Providence Road
Perry, FL 32347