

PRODUCT SPECIFICATIONS	
Diameter	40mm (1.60 in)
Length	102mm (4 in)
Projectile Count	1
Velocity	100 m/s (325 fps)
Minimum Safe Distance <sup>1</sup>	1.5m (5 ft)
Maximum Effective Distance	36.6m (120 ft)
PROJECTICLE SPECIFICATIONS	
Material	Polyurethane
Height	73mm (3 in)
Diameter	40mm (1.6 in)
Weight	24 grams (1.0 oz)
Payload Weight	2 grams OC
Part Number	ALS4006DOC
Warranty	5 years from date of manufacture



1 – When using this round at or near the minimum safe distance, the operator must evaluate the totality of circumstances (i.e. judgment, discretion, common sense) in relation to officer factors/judgment (i.e. subject factors, environmental factors, unknown factors, etc.) to determine whether or not deploying the round is appropriate for the situation.

### PRODUCT DESCRIPTION

The ALS4006DOC REACT round is a direct fire round designed to combine blunt trauma pain compliance with OC irritant upon impact. It is highly accurate and effective across a broad range of distances.

The round is most effective when used within the optimal range of 2-40 yards. Operators should be well trained in the use of Less Lethal munitions regarding shot placement including, but not limited to, factors such as: level of threat, target distance, and clothing. The optimal range allows for accurate targeting of the large muscle groups of the subject providing sufficient pain stimulus while greatly reducing the risk of serious or life-threatening injuries.

### SHIPPING INFORMATION

UN Number	UN0301	<b>WARNING:</b> This round should only be used by individuals properly trained in the use of specialty impact munitions. Serious injury or death may occur if this product is misused in rare or unexpected instances. Individuals should only engage appropriate target areas.
Proper Shipping Name	Ammunition, Tear Producing	
Hazard Class	1.4G	
Quantity per package	52	
Total package weight	8.17kg (18 lb)	
Package type	UN1A2 Steel Drum	
Package dimensions	305mm x 406mm 12 x 16 inches	



4700 Providence Road  
Perry, FL 32347