

PRODUCT SPECIFICATIONS	
Diameter	40mm (1.60 in)
Length	102mm (4 in)
Projectile Count	1
Velocity	122 m/s (400 fps)
Minimum Safe Distance ¹	10m (30 ft)
Maximum Effective Distance	64m (210 ft)
PROJECTICLE SPECIFICATIONS	
Material	Polyurethane
Height	73mm (3 in)
Diameter	40mm (1.6 in)
Weight	24 grams (1.0 oz)
Payload Weight	3 grams CS
Part Number	ALS4006DXCS
Warranty	5 years from date of manufacture



1 – When using this round at or near the minimum safe distance, the operator must evaluate the totality of circumstances (i.e. judgment, discretion, common sense) in relation to officer factors/judgment (i.e. subject factors, environmental factors, unknown factors, etc.) to determine whether or not deploying the round is appropriate for the situation.

PRODUCT DESCRIPTION

The ALS4006DXCS REACT round is an extended range direct fire round designed to combine blunt trauma pain compliance with OC irritant upon impact. It is highly accurate and effective across a broad range of distances.

The round is most effective when used within the optimal range of 10-70 yards. Operators should be well trained in the use of Less Lethal munitions regarding shot placement including, but not limited to, factors such as: level of threat, target distance, and clothing. The optimal range allows for accurate targeting of the large muscle groups of the subject providing sufficient pain stimulus while greatly reducing the risk of serious or life-threatening injuries.

SHIPPING INFORMATION

UN Number	UN0301
Proper Shipping Name	Ammunition, Tear Producing
Hazard Class	1.4G
Quantity per package	52
Total package weight	8.17kg (18 lb)
Package type	UN1A2 Steel Drum
Package dimensions	305mm x 406mm 12 x 16 inches

WARNING: This round should only be used by individuals properly trained in the use of specialty impact munitions. Serious injury or death may occur if this product is misused in rare or unexpected instances. Individuals should only engage appropriate target areas.



4700 Providence Road
Perry, FL 32347