




LITEX IILX02

TECHNICAL SUMMARY & NIJ DATA

THREAT LEVEL

II

STANDARD	NIJ 0101.06
NIJ MODEL	GPBII-3
SERIES	LX02
THREAT LEVEL	II
GENDER	Neutral
AREAL DENSITY	0.90 psf
THINNESS	0.22"
PLY COUNT	21
SIZE RANGE	C1-C5
COMPOSITION	Twaron®/Goldflex® Hybrid
STITCHING	Diamond Quilt, Perimeter Stitch, Shoulder Tack, Bottom Stitch
PANEL COVER	Dual Covered, 2 Ply, 70 Denier Textured Nylon Ripstop with TPU Lamination System
DESICCANT	Patented ProTect® Material
WARRANTY	5 Years



Twaron®

The power of Aramid

Honeywell



BALLISTIC PERFORMANCE AT CERTIFICATION

9mm New V50	1683 fps	.357 Mag New V50	1644 fps
9mm Conditioned V50	1614 fps	.357 Mag Conditioned V50	1613 fps
9mm BFS	30.8 mm	.357 Mag BFS	33.8 mm
9mm New RPI	1870	.357 Mag New RPI	1827
9mm Conditioned RPI	1793	.357 Mag Conditioned RPI	1792

SPECIAL THREAT TESTING

9mm 127gr SXT +P+ RA9TA | .357 SIG 125gr GDHP

Special threat testing conducted at NIJ certified independent laboratory