

Height	19.5"	49.5 cm	
Width	4.50"	11.4 cm	
Firing Mechanism	Spring Loaded Handle with Safety Pin		
Warranty	2 Year Shelf Life		
Canister Material	Seamless Aluminum Rated DOT3ALM		

**MK-46 Mega Unit**: The aluminum canister holding the formulation is fitted with a discharge mechanism consisting of a spring loaded depression valve, aluminum detachable nozzle, pressure gauge, Schrader valve, and hand guard protecting the "squeeze type" actuator. Unit is easily refillable and re-chargeable with the addition of the Schrader valve. The **MK-46 Mega Unit** comes empty and requires refill jugs to use.

Delivery	Ballistic Stream Refills				
Effective Range	Up to 30ft				
Formulation Weight	46oz/1304 grams				
Stock Number	RF01H	RF02H	RF03H	RF04H	
Strength	Level I 10%	Level II 5.5%	Level III 10%	Inert	
T.C. (New) ASTA 21.3 *	0.31%	0.69%	1.25%	None	
T.C. (Old) ASTA 21.1	0.33%	0.72%	1.33%	None	
Scoville Heat Units (SHU)	500,000	2,000,000		Zero	

## 46oz MK-46 Mega Unit



**Formulation:** Oleoresin Capsicum (OC) combined with a **Non-Flammable carrier**. Guardian Protective Devices™ sprays are safe for use with Electro Muscular Disruption (EMD) technology, such as Taser™. UV dye added for easy identification, putting the subject at the scene of incidence.

OC + CS blends are available, custom blends upon request to meet your department requirements.

**Safety:** A steel "pull ring" type safety pin passes through both the discharge mechanism and the actuator to prevent accidental discharge of the formulation. The unit is also fitted with a shielded pressure gauge to protect against accidental damage.

Labeling: All canister labels are wearing water-resistant and contain the following data:

- Individualized Serial Numbers
- Active Ingredient
- Date of Manufacture

· Date of Expiration

- Lot / Batch Number
- Stock Number
- Decontamination Instructions

Packaging: Department of Transportation (DOT) approved commercial packaging.

